

HaloUltra™

The Halo Ultra™ is a robust evacuation chair, designed to accommodate passenger payloads of up to **500lbs/227kg**. Its zipped hammock and footrest, which doubles as a grab handle, provide greater comfort to the passenger and enables a second person to assist in downward evacuations. The Halo Ultra™ has a unique track system which provides a smooth and controlled evacuation, for both the operator and passenger.



ACCOMMODATES
PAYLOADS OF UP TO
500LBS/227KG

Double handed grip

Enhances user operation and provides greater operator control.

Sewn-in safety belt

Secures the passenger into the Halo Ultra™.

Zipped hammock

Dual seating position, zips can be removed to provide a different seating arrangement.

Front grab handles

Enables second person to assist.

Footrest

Provides a secure place for the passenger to rest their feet.

Contoured headrest

Provides passenger comfort and its integrated strap provides additional support.

Unique track system

Self-braking belt controls smoothness and speed of descent.

Kickstand & rear wheels

Deploy for use on flat terrain.

Large 4" castor wheels

Provides stability when descending stairs.



Specification

Halo Ultra™	Folded	Unfolded
Height	43.3"/1100mm	53.9"/1370mm
Width	20.5"/520mm	20.5"/520mm
Depth	9.8"/250mm	44.9"/1140mm
Weight (unladen)	28.6lbs/13kg	
Payload capacity	500lbs/227kg	
Stair Angle	28° - 40°	
Seat Width	20.1"/510mm	
Seat Depth	15.8"/400mm	
Back Support Height	13"/330mm	
Back Support Width	17.7"/450mm	
Minimum Landing Depth	59.1" x 59.1"/1500mm x 1500mm	

Approvals/Accreditations

- FDA Registered
- Designed in accordance with RESNA ED-1
- ISO 9001 and ISO 13485

Benefits

- Easy to use
- 1-2 person operation (dependent on passenger weight)
- Lightweight
- No heavy lifting required
- Lifetime Promise

Includes

- Photoluminescent sign
- Wall mounted hooks
- Dust cover
- User guide



Halo™ Evacuation
70 West Madison Street, Suite 5750, Chicago, IL 60602-4213
inquiries@haloevacuation.com | haloevacuation.com 
+1 866-416-2955

